



Most Widely Accepted and Trusted

# ICC-ES Report

## ESR-2702

ICC-ES | (800) 423-6587 | (562) 699-0543 | www.icc-es.org

Reissued 12/2015  
This report is subject to renewal 12/2016.

**DIVISION: 07 00 00—THERMAL AND MOISTURE PROTECTION**  
**SECTION: 07 11 00—FLUID-APPLIED WATERPROOFING**  
**SECTION: 07 14 00—DAMP-PROOFING**

**REPORT HOLDER:**

**GMX, INC.**

**3800 EAST 91<sup>ST</sup> STREET  
CLEVELAND, OHIO 44105**

**EVALUATION SUBJECT:**

**ULTRA-SHIELD® WB AND BONEDRY™ WPT**



Look for the trusted marks of Conformity!

*“2014 Recipient of Prestigious Western States Seismic Policy Council (WSSPC) Award in Excellence”*



A Subsidiary of  INTERNATIONAL CODE COUNCIL™

*ICC-ES Evaluation Reports are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this report, or as to any product covered by the report.*



**ICC-ES Evaluation Report****ESR-2702**

Reissued December 2015

*This report is subject to renewal December 2016.*[www.icc-es.org](http://www.icc-es.org) | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

**DIVISION: 07 00 00—THERMAL AND MOISTURE  
PROTECTION****Section: 07 11 00—Dampproofing****Section: 07 14 00—Fluid-Applied Waterproofing****REPORT HOLDER:****GMX, INC.****3800 EAST 91<sup>ST</sup> STREET****CLEVELAND, OHIO 44105****(216) 641-7500**[www.gmxwaterproofing.com](http://www.gmxwaterproofing.com)[tcarney@garlandind.com](mailto:tcarney@garlandind.com)**EVALUATION SUBJECT:****ULTRA-SHIELD® WB AND BONE DRY™ WPT****1.0 EVALUATION SCOPE****Compliance with the following codes:**

- 2012, 2009 and 2006 *International Building Code*® (IBC)
- 2012, 2009 and 2006 *International Residential Code*® (IRC)

**Property evaluated:**

- Foundation waterproofing
- Foundation dampproofing

**2.0 USES**

Ultra-Shield® WB and BoneDry® WPT are liquid-applied waterproofing and dampproofing membranes used on the exterior of below-grade parged or unparged masonry and concrete foundation walls. The membranes are alternates to the dampproofing materials specified in 2012 and 2009 IBC Section 1805.2.2, 2006 IBC Section 1807.2.2 and IRC Section R406.1. The membranes are also alternates to the waterproofing materials specified in 2012 and 2009 IBC Section 1805.3.2, 2006 IBC Section 1807.3.2 and IRC 406.2.

**3.0 DESCRIPTION**

Ultra-Shield® WB and BoneDry® WPT are polymer-modified, asphalt waterproofing and dampproofing membranes. Ultra-Shield® WB is identical to BoneDry® WPT. The membranes have a resistance to hydrostatic pressure of 3 psi (20.7 kPa) over a 1/16-inch-wide crack when applied in accordance with Section 4.0 and tested in accordance with ASTM C1306. Ultra-Shield® WB and BoneDry® WPT are available in 5-gallon (18.9 L) pails,

55-gallon (208 L) drums, 275-gallon (1041 L) totes and bulk containers. Shelf life is one year from the date of manufacture, when stored unopened at temperatures between 60°F and 80°F (15.6°C and 26.7°C).

**4.0 INSTALLATION****4.1 General:**

Installation must comply with this report, the applicable code and the manufacturer's published installation instructions. The manufacturer's published installation instructions must be available at the jobsite at all times during installation.

**4.2 Surface Preparation:**

Surfaces of substrates must be structurally sound, clean, dry and free of dust, sand, soil, frost or loose materials. Additionally, there must be no fins, metal projections or any substances that will prevent bonding of the membrane to the surface of the substrate. Voids in masonry or concrete, such as tie-rod holes or honeycombed areas, must be filled with nonshrinking grout or an asphalt-based mastic. When nonshrinking grout is used to fill voids, the grout must be allowed to cure before the membrane is applied. Masonry and concrete must be cured prior to the application of the membrane.

**4.3 Application:**

The ambient air temperature at time of application must be 15°F (-8°C) or greater. Ultra-Shield® WB and BoneDry® WPT are brush-, roller- or spray-applied to the substrate in coats at a coverage rate of 1 gallon per 22.5 square feet (0.56 L/m<sup>2</sup>) for each coat, to achieve a minimum dry film thickness of 40 mils [0.040 inch (1.0 mm)]. The membrane is applied to the exterior vertical surfaces of below-grade foundation walls of parged or unparged masonry and concrete. The membrane must be allowed to cure for a minimum of 24 hours before any backfill or membrane protection is placed against the wall.

**5.0 CONDITIONS OF USE**

The Ultra-Shield® WB and BoneDry® WPT waterproofing membranes described in this report comply with, or are suitable alternative to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

**5.1** Installation must comply with this report, the manufacturer's published installation instructions and the applicable code. In the event of a conflict between the manufacturer's published installation instructions and this report, this report governs.

- 5.2 Application is limited to installations on exterior vertical surfaces of below-grade parged or unparged masonry and concrete foundation walls.
- 5.3 Joints and penetrations of the walls to which Ultra-Shield® WB and BoneDry® WPT are applied must be made watertight in accordance with the applicable code.
- 5.4 When use is in dampproofing applications, a subsurface soil investigation of the level of groundwater at the construction site must be performed to verify the nonexistence of hydrostatic pressure.

#### **6.0 EVIDENCE SUBMITTED**

Data in accordance with the ICC-ES Acceptance Criteria for Cold, Liquid-applied, Below-grade, Exterior

Dampproofing and Waterproofing Materials (AC29), dated June 2011 (editorially revised January 2014).

#### **7.0 IDENTIFICATION**

Each container of Ultra-Shield® WB and BoneDry® WPT described in this report must be identified by a label bearing the manufacturer's name (GMX, Inc.), the product name (Ultra-Shield® WB or BoneDry® WPT), lot number, application instructions and the evaluation report number (ESR-2702).